



## Acceptance Testing Procedures – ClearAccess

ClearAccess version Number: \_\_\_\_\_

Software Install Date: \_\_\_\_\_

ClearAccess Admin code: \_\_\_\_\_

ADF election code: \_\_\_\_\_

ADF voter code: \_\_\_\_\_

ADF pollworker code: \_\_\_\_\_

Printer password: \_\_\_\_\_

Technician: \_\_\_\_\_

Acceptance Test Date: \_\_\_\_\_

Use the following list to ensure all acceptance testing items have been checked and completed for the Clear Design Software.

Criteria	Yes	No	Information noted:	Issues	Resolution
Inspection of the all-in-one and/or two-in-one Dell units reveal no damage.	<input type="checkbox"/>	<input type="checkbox"/>	Computer model number:		
Power on and verify computers are correct model number and have correct OS version.			OS version:		
Inspection of the printers reveals no damage. Verify correct model of printers.	<input type="checkbox"/>	<input type="checkbox"/>	Printer model:		
If a printer with wireless capability is used, verify the printer has been secured via password and the wireless features disabled.	<input type="checkbox"/>	<input type="checkbox"/>			
All parts of the system are included: 1 ClearAccess Ballot Marking Device station 1 Printer 1 Lockable port cover per computer (if used) 1 Kensington lock per computer (if used) 1 USB printer cable per printer	<input type="checkbox"/>	<input type="checkbox"/>			



## Acceptance Testing Procedures – ClearAccess

Criteria	Yes	No	Information noted:	Issues	Resolution
1 power supply or power cord per computer depending on model 1 power cord for the printer USB stick(s) with ADF file(s) 1 EZ-Access 8-Key Keypad per computer 1 Sip and Puff per computer (if applicable) 1 audio headset per computer  All have been inspected to insure there is no damage.					
Charge the UPS as specified in the UPS documentation. Unplug the UPS from the wall to check UPS functionality. (If Available) UPS should show the lack of wall power but give no other faults.	<input type="checkbox"/>	<input type="checkbox"/>			
Verify that Chrome is installed and Chrome's default printer is the correct printer model. Expand Chrome settings to verify it is set to Two-sided, Minimum margins and No Headers or Footers.	<input type="checkbox"/>	<input type="checkbox"/>			
Log in with hardened user, start ClearAccess and verify version number.  Verify that with keyboard removed or disabled (depending on computer model), hardened user cannot access Windows Charms bar or other inappropriate programs.	<input type="checkbox"/>	<input type="checkbox"/>			



## Acceptance Testing Procedures – ClearAccess

Criteria	Yes	No	Information noted:	Issues	Resolution
Verify administrator can log in to ClearAccess with correct access codes.	<input type="checkbox"/>	<input type="checkbox"/>			
Verify administrator can open election contained in ADF file on USB stick.	<input type="checkbox"/>	<input type="checkbox"/>			
Set to election open mode and vote and print a couple of test ballots.	<input type="checkbox"/>	<input type="checkbox"/>			
Verify printed test ballots can be scanned into the ClearCount system and tabulated correctly (see ClearCount Acceptance Test).	<input type="checkbox"/>	<input type="checkbox"/>			
Plug in all input devices and verify devices are detected: touchscreen E-Z Access 8-key keypad Origin Breeze Sip-and-Puff if applicable  Help screens display content for relevant devices	<input type="checkbox"/>	<input type="checkbox"/>			
Verify audio reads the complete screen.	<input type="checkbox"/>	<input type="checkbox"/>			
Verify pollworker can input credentials and reprint ballot if necessary.	<input type="checkbox"/>	<input type="checkbox"/>			
Verify election can be closed.	<input type="checkbox"/>	<input type="checkbox"/>			
Security: If applicable, verify locking Ports and cables are functional. Discuss security seals and placement. (Tamper-proof seals to be applied after official election data files are loaded at a later date.)	<input type="checkbox"/>	<input type="checkbox"/>			



## Acceptance Testing Procedures – ClearAccess

When ClearAccess system passes Acceptance Test, affix to back or underside of ClearAccess Station and printer a label with date of test and initials of person who conducted the test.					

Physical Damage:	
Correctable Parts:	
Functional Issues:	

Software version accepted: \_\_\_\_\_ Date: \_\_\_\_\_

Printed Name: \_\_\_\_\_

Authorized Signature: \_\_\_\_\_